

G60Q

专业播音会议话筒

Professional Broadcast Conference Microphone

G SERIES



参数规格 Specifications

单体	背极式驻极体	Monomer	Back electrode electret
指向性	心型 / 超心型/ 全指向 (选配)	Direction	Cardioid /supercardioid/ omnidirectional (apolegamy)
频率范围	40Hz-16KHz	Frequency range	40Hz-16KHz
灵敏度 (48V/1.5V)	-38dB ±3dB(1dB=1V/Pa at 1KHz)	Sensitivity:(48V/1.5V)	-38dB ±3dB(1dB=1V/Pa at 1KHz)
输出阻抗	600Ω ±20% (at 1KHz)	Input impedance	600Ω ±20% (at 1KHz)
等效噪声级	≤25dBa	Equivalent noise level	≤25dBa
信噪比	70dB (1KHz at 1Pa)	SNR	70dB (1KHz at 1Pa)
最大声压级	130dB/115dB (T.H.D≤1% at 1KHz)	Maximum SPL	130dB/115dB (T.H.D≤1% at 1KHz)
使用电源	48V幻象电源 (48V DC) 2mA	Power supply	48 phantom power(48V DC) 2mA
连接线长	3M (标配) / 外置	Connection line	3M(standard configuration)/ outlay
本体尺寸	底座直径 : 85mm	Size	Base diameter:85mm
总高度	110mm	Total height	110mm
输出接口	三针公卡侬	Input interface	3 PIN male XLR



广州市锐丰智能科技有限公司 A:广东省广州市番禺区市莲路石楼路段10号
T:020-3928 0043 F:020-39280123-8014 E:info@rfintell.com Z:511447 www.rfintell.com

Guangzhou Ruifeng Intelligence Technology Co., Ltd Address: No.10,Shilou Section,Shilian Road,Panyu District,Guangzhou,Guangdong,China
T:+86 2039280083 Mobile: +86 13609092324 F:+86-20-39280123-8014 E: mail:sales@rfintell.com Z:511447 www.rfintell.com